Web Services Policy 1.5 - Framework

W3C Working Draft 31 July 2006

This version:
http://www.w3.org/TR/2006/WD-ws-policy-20060731
Latest version:
http://www.w3.org/TR/ws-policy
Editors:
Asir S Vedamuthu, Microsoft Corporation
David Orchard, BEA Systems, Inc.
Maryann Hondo, IBM Corporation
Toufic Boubez, Layer 7 Technologies
Prasad Yendluri, webMethods, Inc.

This document is also available in these non-normative formats: PDF, PostScript, XML, and plain text.

Copyright © 2006 World Wide Web ConsortiumW3C® (Massachusetts Institute of TechnologyMIT, European Research Consortium for Informatics and MathematicsERCIM, Keio), All Rights Reserved. W3C liability, trademark and document use rules apply.

Abstract

The Web Services Policy 1.5 - Framework provides a general purpose model and corresponding syntax to describe the policies of a Web Service.

Web Services Policy Framework defines a base set of constructs that can be used and extended by other Web services specifications to describe a broad range of service requirements and capabilities.

Status of this Document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the W3C technical reports index at http://www.w3.org/TR/.

This is the First Public Working Draft of the Web Services Policy 1.5 - Framework specification. This Working Draft was produced by the members of the Web Services Policy Working Group. The Working Group expects to advance this Working Draft to Recommendation Status. It represents a transcription of the original Member Submission specification into the W3C style. Note that this Working Draft does not necessarily represent a consensus of the Working Group. Technical discussion related to the development

of this specification takes place on the public-ws-policy mailing list (archive).

Publication as a Working Draft does not imply endorsement by the W3C Membership. This is a draft document and may be updated, replaced or obsoleted by other documents at any time. It is inappropriate to cite this document as other than work in progress.

This document was produced by a group operating under the 5 February 2004 W3C Patent Policy. W3C maintains a public list of any patent disclosures made in connection with the deliverables of the group; that page also includes instructions for disclosing a patent. An individual who has actual knowledge of a patent which the individual believes contains Essential Claim(s) must disclose the information in accordance with section 6 of the W3C Patent Policy.

Table of Contents

1. Introduction [p.3]
   1.1 Goals [p.4]
2. Notations and Terminology [p.4]
   2.1 Notational Conventions [p.4]
   2.2 XML Namespaces [p.5]
   2.3 Terminology [p.6]
3. Policy Model [p.6]
   3.1 Policy Assertion [p.7]
   3.2 Policy Alternative [p.7]
   3.3 Policy [p.8]
   3.4 Web services [p.8]
4. Policy Expression [p.8]
   4.1 Normal Form Policy Expression [p.9]
   4.2 Policy Identification [p.10]
   4.3 Compact Policy Expression [p.11]
      4.3.1 Optional Policy Assertions [p.11]
      4.3.2 Policy Assertion Nesting [p.12]
      4.3.3 Policy Operators [p.15]
      4.3.4 Policy Inclusion [p.19]
   4.4 Policy Intersection [p.21]
5. Security Considerations [p.23]

Appendices

A. References [p.23]
   A.1 Normative References [p.23]
   A.2 Other References [p.24]
B. Acknowledgements [p.25] (Non-Normative)
C. Web Services Policy 1.5 - Framework Change Log [p.26] (Non-Normative)

1. Introduction

Web Services Policy 1.5 - Framework provides a flexible and extensible language for expressing the capabilities, requirements, and general characteristics of entities in an XML Web services-based system. Web Services Policy 1.5 - Framework defines a framework and a model for the expression of these properties as policies.

Web Services Policy 1.5 - Framework defines a policy to be a collection of policy alternatives, where each policy alternative is a collection of policy assertions. Some policy assertions specify traditional requirements and capabilities that will ultimately manifest on the wire (e.g., authentication scheme, transport protocol selection). Other policy assertions have no wire manifestation yet are critical to proper service selection and usage (e.g., privacy policy, QoS characteristics). Web Services Policy 1.5 - Framework provides a single policy language to allow both kinds of assertions to be reasoned about in a consistent manner.

Web Services Policy 1.5 - Framework does not specify how policies are discovered or attached to a Web service. Other specifications are free to define technology-specific mechanisms for associating policy with various entities and resources. Web Services Policy 1.5 - Attachment [*Web Services Policy Attachment [p.25]*] defines such mechanisms, especially for associating policy with arbitrary XML elements [*XML 1.0 [p.24]*], WSDL artifacts [*WSDL 1.1 [p.25]* , *WSDL 2.0 Core Language [p.25]*], and UDDI elements [*UDDI API 2.0 [p.24]* , *UDDI Data Structure 2.0 [p.24]* , *UDDI 3.0 [p.25]*].

The following example illustrates a security policy using assertions defined in WS-SecurityPolicy [*WS-SecurityPolicy [p.25]*]:

Example 1-1. Use of Web Services Policy with security policy assertions.

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <wsp:ExactlyOne>
(03)      <sp:Basic256Rsa15 />
(04)      <sp:TripleDesRsa15 />
(05)    </wsp:ExactlyOne>
(06) </wsp:Policy>
```

Lines (01-06) represent a policy for the algorithm suite required for performing cryptographic operations with symmetric or asymmetric key-based security tokens.

Lines (02-05) illustrate the `ExactlyOne` policy operator. Policy operators group policy assertions into policy alternatives. A valid interpretation of the policy above would be that an invocation of a Web service uses one of the algorithm suite assertions (Lines 03-04) specified.

1.1 Goals

The goal of Web Services Policy 1.5 - Framework is to provide the mechanisms needed to enable Web services applications to specify policy information. Specifically, this specification defines the following:

- An XML Infoset called a *policy expression* that contains domain-specific, Web Service policy information.
- A core set of constructs to indicate how choices and/or combinations of domain-specific policy assertions apply in a Web services environment.

Web Services Policy 1.5 - Framework is designed to work with the general Web services framework, including WSDL service descriptions [*WSDL 1.1 [p.25]* , *WSDL 2.0 Core Language [p.25]*] and UDDI service registrations [*UDDI API 2.0 [p.24]* , *UDDI Data Structure 2.0 [p.24]* , *UDDI 3.0 [p.25]*].

2. Notations and Terminology

This section specifies the notations, namespaces, and terminology used in this specification.

2.1 Notational Conventions

This specification uses the following syntax within normative outlines:

- The syntax appears as an XML instance, but values in *italics* indicate data types instead of literal values.
- Characters are appended to elements and attributes to indicate cardinality:
  - "?" (0 or 1)
  - "*" (0 or more)
  - "+" (1 or more)
- The character "|" is used to indicate a choice between alternatives.
- The characters "(" and ")" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.
- This document relies on the XML Information Set [*XML Information Set [p.24]*]. Information items properties are indicated by the style **[infoset property]**.
- XML namespace prefixes (see Table 2-1 [p.5]) are used to indicate the namespace of the element or attribute being defined.
- The ellipses characters "…" are used to indicate a point of extensibility that allows other Element or Attribute Information Items. Information Items MAY be added at the indicated extension points but MUST NOT contradict the semantics of the element information item indicated by the **[parent]** or

[owner] property of the extension. If a processor does not recognize an Attribute Information Item, the processor SHOULD ignore it; if a processor does not recognize an Element Information Item, the processor SHOULD treat it as an assertion.

Normative text within this specification takes precedence over normative outlines, which in turn take precedence over the XML Schema [*XML Schema Structures [p.24]*] descriptions.

2.2 XML Namespaces

This specification uses a number of namespace prefixes throughout; they are listed in Table 2-1 [p.5] . Note that the choice of any namespace prefix is arbitrary and not semantically significant (see [*XML Namespaces [p.24]*]).

Table 2-1. Prefixes and Namespaces used in this specification

Prefix	Namespace	Specification
`sp`	http://schemas.xmlsoap.org/ws/2005/07/securitypolicy	[*WS-SecurityPolicy [p.25]*]
`wsp`	`http://www.w3.org/2006/07/ws-policy`	This specification
`wsu`	`http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd`	[*WS-Security 2004 [p.23]*]
`xs`	`http://www.w3.org/2001/XMLSchema`	[*XML Schema Structures [p.24]*]

All information items defined by this specification are identified by the XML namespace URI [*XML Namespaces [p.24]*] `http://www.w3.org/2006/07/ws-policy`. A normative XML Schema [*XML Schema Structures [p.24]* , *XML Schema Datatypes [p.24]*] document can be obtained by dereferencing the XML namespace URI.

It is the intent of the W3C Web Services Policy Working Group that the Web Services Policy 1.5 - Framework and Web Services Policy 1.5 - Attachment XML namespace URI will not change arbitrarily with each subsequent revision of the corresponding XML Schema documents but rather change only when a subsequent revision, published as a WD, CR or PR draft results in non-backwardly compatible changes from a previously published WD, CR or PR draft of the specification.

Under this policy, the following are examples of backwards compatible changes that would not result in assignment of a new XML namespace URI:

- Addition of new global element, attribute, complexType and simpleType definitions.
- Addition of new elements or attributes in locations covered by a previously specified wildcard.
- Modifications to the pattern facet of a type definition for which the value-space of the previous definition remains valid or for which the value-space of the preponderance of instance would remain valid.

- Modifications to the cardinality of elements for which the value-space of possible instance documents conformant to the previous revision of the schema would still be valid with regards to the revised cardinality rule.

2.3 Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [*IETF RFC 2119 [p.23]*].

We introduce the following terms that are used throughout this document:

[Definition: A **policy** is a collection of policy alternatives [p.6] .]

[Definition: A **policy alternative** is a collection of policy assertions [p.6] .]

[Definition: A **policy assertion** represents an individual requirement, capability, or other property of a behavior.]

[Definition: A **policy assertion type** represents a class of policy assertions [p.6] and implies a schema for the assertion and assertion-specific semantics.]

[Definition: A **policy assertion parameter** qualifies the behavior indicated by a policy assertion [p.6] .]

[Definition: A **policy vocabulary** of a policy is the set of all policy assertion types [p.6] used in a policy.]

[Definition: A **policy expression** is an XML Infoset representation of a policy [p.6] , either in a normal form or in an equivalent compact form.]

[Definition: A **policy subject** is an entity (e.g., an endpoint, message, resource, interaction) with which a policy [p.6] can be associated.]

[Definition: A **policy scope** is a collection of policy subjects [p.6] to which a policy may apply.]

[Definition: A **policy attachment** is a mechanism for associating policy [p.6] with one or more policy scopes [p.6] .]

3. Policy Model

This section defines an abstract model for policies and for operations upon policies.

This abstract model is independent of how it is represented as an XML Infoset.

3.1 Policy Assertion

A policy assertion [p.6] identifies a behavior that is a requirement (or capability) of a policy subject [p.6] . Assertions indicate domain-specific (e.g., security, transactions) semantics and are expected to be defined in separate, domain-specific specifications.

Assertions are strongly typed by the domain authors that define them. The policy assertion type [p.6] is identified only by the XML Infoset **[namespace name]** and **[local name]** properties (that is, the qualified name or QName) of the root Element Information Item representing the assertion. Assertions of a given type MUST be consistently interpreted independent of their policy subjects [p.6] .

Domain authors MAY define that an assertion contains a policy expression [p.6] as one of its **[children]**. Policy expression nesting is used by domain authors to further qualify one or more specific aspects of the original assertion. For example, security policy domain authors may define an assertion describing a set of security algorithms to qualify the specific behavior of a security binding assertion.

The XML Infoset of an assertion MAY contain a non-empty [attributes] property and/or a non-empty **[children]** property. Such content MAY be used to parameterize the behavior indicated by the assertion. For example, an assertion identifying support for a specific reliable messaging mechanism might include an attribute information item to indicate how long an endpoint will wait before sending an acknowledgement.

Domain authors should be cognizant of the processing requirements when defining complex assertions containing additional assertion content or nested policy expressions. Specifically, domain authors are encouraged to consider when the identity of the root Element Information Item alone is enough to convey the requirement (capability).

3.2 Policy Alternative

A policy alternative [p.6] is a logical construct which represents a potentially empty collection of policy assertions [p.6] . An alternative with zero assertions indicates no behaviors. An alternative with one or more assertions indicates behaviors implied by those, and only those assertions.

The vocabulary of a policy alternative is the set of all policy assertion types [p.6] within the alternative. The vocabulary of a policy [p.6] is the set of all assertion types used in all the policy alternatives in the policy. An assertion whose type is part of the policy's vocabulary but is not included in an alternative is explicitly prohibited by the alternative.

Assertions within an alternative are not ordered, and thus aspects such as the order in which behaviors (indicated by assertions) are applied to a subject [p.6] are beyond the scope of this specification.

A policy alternative MAY contain multiple assertions of the same type. Mechanisms for determining the aggregate behavior indicated by the assertions (and their Post-Schema-Validation Infoset (PSVI) content, if any) are specific to the assertion type and are outside the scope of this document.

3.3 Policy

At the abstract level a policy [p.6] is a potentially empty collection of policy alternatives [p.6] . A policy with zero alternatives contains no choices; a policy with one or more alternatives indicates choice in requirements (or capabilities) within the policy.

Alternatives are not ordered, and thus aspects such as preferences between alternatives in a given context are beyond the scope of this specification.

Alternatives within a policy may differ significantly in terms of the behaviors they indicate. Conversely, alternatives within a policy may be very similar. In either case, the value or suitability of an alternative is generally a function of the semantics of assertions within the alternative and is therefore beyond the scope of this specification.

3.4 Web services

Applied in the Web services model, policy [p.6] is used to convey conditions on an interaction between two Web service endpoints. Satisfying assertions in the policy usually results in behavior that reflects these conditions. Typically, the provider of a Web service exposes a policy to convey conditions under which it provides the service. A requester might use this policy to decide whether or not to use the service. A requester may choose any alternative since each is a valid configuration for interaction with the service, but a requester MUST choose only a single alternative for an interaction with a service since each represents an alternative configuration.

A policy assertion [p.6] is *supported* by a requester if and only if the requester satisfies the requirement (or accommodates the capability) corresponding to the assertion. A policy alternative [p.6] is *supported* by a requester if and only if the requester supports all the assertions in the alternative. And, a policy [p.6] is *supported* by a requester if and only if the requester supports at least one of the alternatives in the policy. Note that although policy alternatives are meant to be mutually exclusive, it cannot be decided in general whether or not more than one alternative can be supported at the same time.

Note that a requester may be able to support a policy even if the requester does not understand the type [p.6] of each assertion in the vocabulary of the policy [p.6] ; the requester only has to understand the type of each assertion in the vocabulary of a policy alternative [p.6] . This characteristic is crucial to versioning and incremental deployment of new assertions because this allows a provider’s policy to include new assertions in new alternatives while allowing requesters to continue to use old alternatives in a backward-compatible manner.

4. Policy Expression

To convey policy in an interoperable form, a policy expression [p.6] is an XML Infoset representation of a policy. The normal form policy expression is the most straightforward Infoset; equivalent, alternative Infosets allow compactly expressing a policy through a number of constructs.

4.1 Normal Form Policy Expression

To facilitate interoperability, this specification defines a normal form for policy expressions [p.6] that is a straightforward XML Infoset representation of a policy, enumerating each of its alternatives that in turn enumerate each of their assertions. The schema outline for the normal form of a policy expression is as follows:

```
<wsp:Policy ... >
  <wsp:ExactlyOne>
    ( <wsp:All> ( <Assertion ...> ... </Assertion> )* </wsp:All> )*
  </wsp:ExactlyOne>
</wsp:Policy>
```

The following describes the Element Information Items defined in the schema outline above:

`/wsp:Policy`

A policy expression.

`/wsp:Policy/wsp:ExactlyOne`

A collection of policy alternatives. If there are no Element Information Items in the **[children]** property, there are no admissible policy alternatives, i.e., no behavior is admissible.

`/wsp:Policy/wsp:ExactlyOne/wsp:All`

A policy alternative; a collection of policy assertions. If there are no Element Information Items in the **[children]** property, this is an admissible policy alternative that is empty, i.e., no behavior is specified.

`/wsp:Policy/wsp:ExactlyOne/wsp:All/*`

XML Infoset representation of a policy assertion.

If an assertion [p.6] in the normal form of a policy expression contains a nested policy expression, the nested policy expression MUST contain at most one policy alternative.

To simplify processing and improve interoperability, the normal form of a policy expression should be used where practical.

For example, the following is the normal form of the policy expression example introduced earlier.

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <wsp:ExactlyOne>
(03)      <wsp:All>
(04)        <sp:Basic256Rsa15 />
(05)      </wsp:All>
(06)      <wsp:All>
```

```
(07)        <sp:TripleDesRsa15 />
(08)      </wsp:All>
(09)    </wsp:ExactlyOne>
(10) </wsp:Policy>
```

Lines (02-05) and Lines (06-08) express the two alternatives in the policy. If the first alternative is selected, only the Basic 256 RSA 15 algorithm suite [*WS-SecurityPolicy [p.25]*] is supported; conversely, if the second alternative is selected, only the 3DES RSA 15 algorithm suite is supported.

4.2 Policy Identification

A policy expression [p.6] MAY be associated with a URI [*IETF RFC 3986 [p.23]*]. The schema outline for attributes to associate a URI is as follows:

```
<wsp:Policy ( Name="xs:anyURI" )?
            ( wsu:Id="xs:ID" )?
            ... >
  ...
</wsp:Policy>
```

The following describes the Attribute Information Items listed and defined in the schema outline above:

`/wsp:Policy/@Name`

> The identity of the policy expression as an absolute URI [*IETF RFC 3986 [p.23]*]. If omitted, there is no implied value. This URI MAY be used to refer to a policy from other XML documents using a policy attachment [p.6] mechanism such as those defined in WS-PolicyAttachment [*Web Services Policy Attachment [p.25]*].

`/wsp:Policy/@wsu:Id`

> The identity of the policy expression as an `ID` within the enclosing XML document. If omitted, there is no implied value. To refer to this policy expression, a URI-reference MAY be formed using this value per Section 4.2 of WS-Security [*WS-Security 2004 [p.23]*].

The following example illustrates how to associate a policy expression with the absolute URI `"http://www.example.com/policies/P1"`:

```
(01) <wsp:Policy
        Name="http://www.example.com/policies/P1"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)   <!-- Details omitted for readability -->
(03) </wsp:Policy>
```

The following example illustrates how to associate a policy expression with the URI-reference `"#P1"`:

```
(01) <wsp:Policy
       wsu:Id="P1"
       xmlns:wsp="http://www.w3.org/2006/07/ws-policy"
       xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" >
(02)   <!-- Details omitted for readability -->
(03) </wsp:Policy>
```

4.3 Compact Policy Expression

To express a policy in a more compact form while still using the XML Infoset, this specification defines three constructs: an attribute to decorate an assertion [p.6] , semantics for recursively nested policy operators, and a policy reference/inclusion mechanism. Each is described in the subsections below.

To interpret a compact policy expression in an interoperable form, a compact expression may be converted to the corresponding normal form expression by the following procedure:

1. Start with the **[document element]** property D of the Document Information Item of the policy expression. The **[namespace name]** of D is always `"http://www.w3.org/2006/07/ws-policy"`. In the base case, the **[local name]** property of D is `"Policy"`; in the recursive case, the **[local name]** property of D is `"Policy"`, `"ExactlyOne"`, or `"All"`.

2. Expand Element Information Items in the **[children]** property of D that are policy references per Section **4.3.4 Policy Inclusion** [p.19] .

3. Convert each Element Information Item C in the **[children]** property of D into normal form.

    1. If the **[namespace name]** property of C is `"http://www.w3.org/2006/07/ws-policy"` and the **[local name]** property of C is `"Policy"`, `"ExactlyOne"`, or `"All"`, C is an expression of a policy operator; normalize C by recursively applying this procedure.

    2. Otherwise the Element Information Item C is an assertion; normalize C per Sections **4.3.1 Optional Policy Assertions** [p.11] and **4.3.2 Policy Assertion Nesting** [p.12] .

4. Apply the policy operator indicated by D to the normalized Element Information Items in its **[children]** property and construct a normal form per Section **4.3.3 Policy Operators** [p.15] .

Note that an implementation may use a more efficient procedure and is not required to explicitly convert a compact expression into the normal form as long as the processing results are indistinguishable from doing so.

4.3.1 Optional Policy Assertions

To indicate that a policy assertion [p.6] is optional, this specification defines an attribute that is a syntactic shortcut for expressing policy alternatives with and without the assertion. The schema outline for this attribute is as follows:

```
<Assertion ( wsp:Optional="xs:boolean" )? ...> ... </Assertion>
```

The following describes the Attribute Information Item defined in the schema outline above:

`/Assertion/@wsp:Optional`

If true, the expression of the assertion is semantically equivalent to the following:

```
<wsp:ExactlyOne>
  <wsp:All> <Assertion ...> ... </Assertion> </wsp:All>
  <wsp:All />
</wsp:ExactlyOne>
```

If false, the expression of the assertion is semantically equivalent to the following:

```
<wsp:ExactlyOne>
  <wsp:All> <Assertion ...> ... </Assertion> </wsp:All>
</wsp:ExactlyOne>
```

Omitting this attribute is semantically equivalent to including it with a value of false. Policy expressions should not include this attribute with a value of false, but policy parsers must accept this attribute with a value of false.

For example, the following compact policy expression:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <sp:IncludeTimestamp wsp:Optional="true" />
(03) </wsp:Policy>
```

is equivalent to the following normal form policy expression:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <wsp:ExactlyOne>
(03)      <wsp:All>
(04)        <sp:IncludeTimestamp />
(05)      </wsp:All>
(06)      <wsp:All />
(07)    </wsp:ExactlyOne>
(08) </wsp:Policy>
```

The `@wsp:Optional` attribute in Line (02) of the first policy expression indicates that the assertion in Line (02) is to be included in a policy alternative whilst excluded from another; it is included in Lines (03-05) and excluded in Line (06). Note that `@wsp:Optional` does not appear in the normal form of a policy expression.

4.3.2 Policy Assertion Nesting

Any policy assertion [p.6] MAY contain a nested policy expression [p.6] . The schema outline for a nested policy expression is:

```
<Assertion ...>
  ...
  ( <wsp:Policy ...> ... </wsp:Policy> )?
  ...
</Assertion>
```

The following describes additional processing constraints on the outline listed above:

`/Assertion/wsp:Policy`

> This indicates that the assertion contains a nested policy expression. If there is no `wsp:Policy` Element Information Item in the **[children]** property, the assertion has no nested policy expression.
>
> Note: if the schema outline for an assertion type requires a nested policy expression but the assertion does not further qualify one or more aspects of the behavior indicated by the assertion type (i.e., no assertions are needed in the nested policy expression), the assertion MUST include an empty `<wsp:Policy/>` Element Information Item in its **[children]** property; as explained in Section **4.3.3 Policy Operators** [p.15] , this is equivalent to a nested policy expression with a single alternative that has zero assertions. If this is not done then two assertions of the same type will not be compatible and intersection may fail (see Section **4.4 Policy Intersection** [p.21]).

/Assertion/*/wsp:Policy

> This specification does not define processing for arbitrary `wsp:Policy` Element Information Items in the descendants of an assertion, e.g., in the **[children]** property of one of the **[children]** as in `<Lorem><Ipsum><wsp:Policy> ... </wsp:Policy></Ipsum></Lorem>`.

Policy assertions containing a nested policy expression are normalized recursively. The nesting of a policy expression (and a `wsp:Policy` child) is retained in the normal form, but in the normal form, each nested policy expression contains at most one policy alternative. If an assertion A contains a nested policy expression E, and if E contains more than one policy alternative, A is duplicated such that there are as many instances of A as choices in E, and the nested policy expression of a duplicate A contains a single choice. This process is applied recursively to the assertions within those choices and to their nested policy expression, if any. Intuitively, if a compact policy is thought of as a tree whose branches have branches etc, in the normal form, a policy is a stump with straight vines.

For example, consider the following compact nested policy expression:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <sp:TransportBinding>
(03)      <wsp:Policy>
(04)        <sp:AlgorithmSuite>
(05)          <wsp:Policy>
(06)            <wsp:ExactlyOne>
(07)              <sp:Basic256Rsa15 />
(08)              <sp:TripleDesRsa15 />
(09)            </wsp:ExactlyOne>
(10)          </wsp:Policy>
(11)        </sp:AlgorithmSuite>
(12)        <sp:TransportToken>
(13)          <wsp:Policy>
(14)            <sp:HttpsToken RequireClientCertificate="false" />
(15)          </wsp:Policy>
(16)        </sp:TransportToken>
```

```
          <!-- Details omitted for readability -->
(17)      </wsp:Policy>
(18)    </sp:TransportBinding>
(19) </wsp:Policy>
```

Lines (02-18) in this policy expression contain a single transport binding security policy assertion; within its nested policy expression (Lines 03-17), is an algorithm suite assertion (Lines 04-11) whose nested policy expression (Lines 05-10) contains two policy alternatives (Lines 07-08). Generally, a nested policy expression implies recursive processing; in the example above, the behavior indicated by the transport binding assertion requires the behavior indicated by one of the assertions within the algorithm suite assertion.

The normalized form of this policy is equivalent to the following:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)   <wsp:ExactlyOne>
(03)     <wsp:All>
(04)       <sp:TransportBinding>
(05)         <wsp:Policy>
(06)           <sp:AlgorithmSuite>
(07)             <wsp:Policy>
(08)               <sp:Basic256Rsa15 />
(09)             </wsp:Policy>
(10)           </sp:AlgorithmSuite>
(11)           <sp:TransportToken>
(12)             <wsp:Policy>
(13)               <sp:HttpsToken RequireClientCertificate="false" />
(14)             </wsp:Policy>
(15)           </sp:TransportToken>
               <!-- Details omitted for readability -->
(16)         </wsp:Policy>
(17)       </sp:TransportBinding>
(18)     </wsp:All>
(19)     <wsp:All>
(20)       <sp:TransportBinding>
(21)         <wsp:Policy>
(22)           <sp:AlgorithmSuite>
(23)             <wsp:Policy>
(24)               <sp:TripleDesRsa15 />
(25)             </wsp:Policy>
(26)           </sp:AlgorithmSuite>
(27)           <sp:TransportToken>
(28)             <wsp:Policy>
(29)               <sp:HttpsToken RequireClientCertificate="false" />
(30)             </wsp:Policy>
(31)           </sp:TransportToken>
               <!-- Details omitted for readability -->
(32)         </wsp:Policy>
(33)       </sp:TransportBinding>
(34)     </wsp:All>
(35)   </wsp:ExactlyOne>
(36) </wsp:Policy>
```

In the listing above, the transport binding and its nested policy expression have been duplicated once for each of the nested alternatives in Lines (07-08) of the compact policy. The first alternative (Lines 03-18) contains a single nested algorithm suite alternative (Line 08) as does the second alternative (Lines 19-34 and 24).

4.3.3 Policy Operators

To compactly express complex policies, policy operators MAY be recursively nested; that is, one or more instances of `wsp:Policy` , `wsp:All` , and/or `wsp:ExactlyOne` MAY be nested within `wsp:Policy` , `wsp:All` , and/or `wsp:ExactlyOne` .

The following rules are used to transform a compact policy expression into a normal form policy expression:

Equivalence

`wsp:Policy` is equivalent to `wsp:All` .

Empty

- `<wsp:All />` expresses a policy with zero policy assertions. Note that since `wsp:Policy` is equivalent to `wsp:All` , `<wsp:Policy />` is therefore equivalent to `<wsp:All />`, i.e., a policy alternative with zero assertions.
- `<wsp:ExactlyOne />` expresses a policy with zero policy alternatives.

Commutative

In line with the previous statements that policy assertions within a policy alternative and policy alternatives within a policy are not ordered (see **3.2 Policy Alternative** [p.7] and **3.3 Policy** [p.8] , respectively), `wsp:All` and `wsp:ExactlyOne` are commutative. For example,

```
<wsp:All> <!-- assertion 1 --> <!-- assertion 2 --> </wsp:All>
```

is equivalent to:

```
<wsp:All> <!-- assertion 2 --> <!-- assertion 1 --> </wsp:All>
```

and:

```
<wsp:ExactlyOne>
  <!-- assertion 1 --> <!-- assertion 2 -->
</wsp:ExactlyOne>
```

is equivalent to:

```
<wsp:ExactlyOne>
  <!-- assertion 2 --> <!-- assertion 1 -->
</wsp:ExactlyOne>
```

Associative

`wsp:All` and `wsp:ExactlyOne` are associative. For example,

```
<wsp:All>
  <!-- assertion 1 -->
  <wsp:All> <!-- assertion 2 --> </wsp:All>
</wsp:All>
```

is equivalent to:

```
<wsp:All> <!-- assertion 1 --> <!-- assertion 2 --> </wsp:All>
```

and:

```
<wsp:ExactlyOne>
  <!-- assertion 1 -->
  <wsp:ExactlyOne> <!-- assertion 2 --> </wsp:ExactlyOne>
</wsp:ExactlyOne>
```

is equivalent to:

```
<wsp:ExactlyOne>
  <!-- assertion 1 --> <!-- assertion 2 -->
</wsp:ExactlyOne>
```

Idempotent

`wsp:All` and `wsp:ExactlyOne` are idempotent. For example,

```
<wsp:All>
  <wsp:All> <!-- assertion 1 --> <!-- assertion 2 --> </wsp:All>
</wsp:All>
```

is equivalent to:

```
<wsp:All> <!-- assertion 1 --> <!-- assertion 2 --> </wsp:All>
```

and:

```
<wsp:ExactlyOne>
  <wsp:ExactlyOne>
    <!-- assertion 1 --> <!-- assertion 2 -->
  </wsp:ExactlyOne>
</wsp:ExactlyOne>
```

is equivalent to:

```
<wsp:ExactlyOne>
  <!-- assertion 1 --> <!-- assertion 2 -->
</wsp:ExactlyOne>
```

Distributive

`wsp:All` distributes over `wsp:ExactlyOne` . For example,

```
<wsp:All>
  <wsp:ExactlyOne>
    <!-- assertion 1 -->
    <!-- assertion 2 -->
  </wsp:ExactlyOne>
</wsp:All>
```

is equivalent to:

```
<wsp:ExactlyOne>
  <wsp:All>
    <!-- assertion 1 -->
  </wsp:All>
  <wsp:All>
    <!-- assertion 2 -->
  </wsp:All>
</wsp:ExactlyOne>
```

Similarly,

```
<wsp:All>
  <wsp:ExactlyOne>
    <!-- assertion 1 -->
    <!-- assertion 2 -->
  </wsp:ExactlyOne>
  <wsp:ExactlyOne>
    <!-- assertion 3 -->
    <!-- assertion 4 -->
  </wsp:ExactlyOne>
</wsp:All>
```

is equivalent to:

```
<wsp:ExactlyOne>
  <wsp:All><!-- assertion 1 --><!-- assertion 3 --></wsp:All>
  <wsp:All><!-- assertion 1 --><!-- assertion 4 --></wsp:All>
  <wsp:All><!-- assertion 2 --><!-- assertion 3 --></wsp:All>
  <wsp:All><!-- assertion 2 --><!-- assertion 4 --></wsp:All>
</wsp:ExactlyOne>
```

Distributing `wsp:All` over an empty `wsp:ExactlyOne` is equivalent to no alternatives. For example,

```
<wsp:All>
  <wsp:ExactlyOne>
    <!-- assertion 1 -->
    <!-- assertion 2 -->
  </wsp:ExactlyOne>
  <wsp:ExactlyOne />
</wsp:All>
```

is equivalent to:

```
<wsp:ExactlyOne />
```

For example, given the following compact policy expression:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <sp:RequireDerivedKeys wsp:Optional="true" />
(03)    <wsp:ExactlyOne>
(04)      <sp:WssUsernameToken10 />
(05)      <sp:WssUsernameToken11 />
(06)    </wsp:ExactlyOne>
(07) </wsp:Policy>
```

Applying Section **4.3.1 Optional Policy Assertions** [p.11] to `@wsp:Optional` in Line (02), and distributing `wsp:All` over `wsp:ExactlyOne` per Section **4.3.3 Policy Operators** [p.15] for the assertions in Lines (04-05) yields:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <wsp:ExactlyOne>
(03)      <wsp:All> <!-- @wsp:Optional alternative with assertion -->
(04)        <sp:RequireDerivedKeys />
(05)      </wsp:All>
(06)      <wsp:All /> <!-- @wsp:Optional alternative without -->
(07)    </wsp:ExactlyOne>
(08)    <wsp:ExactlyOne>
(09)      <wsp:All>
(10)        <sp:WssUsernameToken10 />
(11)      </wsp:All>
(12)      <wsp:All>
(13)        <sp:WssUsernameToken11 />
(14)      </wsp:All>
(15)    </wsp:ExactlyOne>
(16) </wsp:Policy>
```

Note that the assertion listed in Line (02) in the first listing expands into the two alternatives in Lines (03-06) in the second listing.

Finally, noting that `wsp:Policy` is equivalent to `wsp:All` , and distributing `wsp:All` over `wsp:ExactlyOne` yields the following normal form policy expression:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)    <wsp:ExactlyOne>
(03)      <wsp:All>
(04)        <sp:RequireDerivedKeys />
(05)        <sp:WssUsernameToken10 />
(06)      </wsp:All>
(07)      <wsp:All>
(08)        <sp:RequireDerivedKeys />
```

```
(09)       <sp:WssUsernameToken11 />
(10)     </wsp:All>
(11)     <wsp:All>
(12)       <sp:WssUsernameToken10 />
(13)     </wsp:All>
(14)     <wsp:All>
(15)       <sp:WssUsernameToken11 />
(16)     </wsp:All>
(17)   </wsp:ExactlyOne>
(18) </wsp:Policy>
```

Note that the two alternatives listed in Lines (03-06) in the second listing are combined with the two alternatives listed in Lines (09-14) in the second listing to create four alternatives in the normalized policy, Lines (03-06), (07-10), (11-13), and (14-16).

4.3.4 Policy Inclusion

In order to share assertions [p.6] across policy expressions [p.6] , the `wsp:PolicyReference` element MAY be present anywhere a policy assertion is allowed inside a policy expression. This element is used to include the content of one policy expression in another policy expression.

When a `wsp:PolicyReference` element references a `wsp:Policy` element, then the semantics of inclusion are simply to replace the `wsp:PolicyReference` element with a `wsp:All` element whose **[children]** property is the same as the **[children]** property of the referenced `wsp:Policy` element. That is, the contents of the referenced policy *conceptually replace* the `wsp:PolicyReference` element and are wrapped in a `wsp:All` operator. Using the `wsp:PolicyReference` element, a policy expression MUST NOT reference itself either directly or indirectly. (Note: References that have a `@Digest` attribute SHOULD be validated before being included.)

The schema outline for the `wsp:PolicyReference` element is as follows:

```
<wsp:Policy>
  ...
  <wsp:PolicyReference
      URI="xs:anyURI"
    ( Digest="xs:base64Binary" ( DigestAlgorithm="xs:anyURI" )? )?
      ... />
  ...
</wsp:Policy>
```

The following describes the Attribute and Element Information Items defined in the schema outline above:

`/wsp:Policy/.../wsp:PolicyReference`

This element references a policy expression that is being included.

`/wsp:Policy/.../wsp:PolicyReference/@URI`

This attribute references a policy expression by URI. For a policy expression within the same XML Document, the reference SHOULD be a URI-reference to a policy expression identified by an `ID`. For an external policy expression, there is no requirement that the URI be resolvable; retrieval mech-

anisms are beyond the scope of this specification. After retrieval, there is no requirement to check that the retrieved policy expression is associated (Section **4.2 Policy Identification** [p.10]) with this URI. The URI included in the retrieved policy expression, if any, MAY be different than the URI used to retrieve the policy expression.

`/wsp:Policy/.../wsp:PolicyReference/@Digest`

This optional attribute specifies the digest of the referenced policy expression. This is used to ensure the included policy is the expected policy. If omitted, there is no implied value.

`/wsp:Policy/.../wsp:PolicyReference/@DigestAlgorithm`

This optional URI attribute specifies the digest algorithms being used. This specification predefines the default algorithm below, although additional algorithms can be expressed.

URI	Description
`http://www.w3.org/2006/07/ws-policy/Sha1Exc` (implied)	The digest is a SHA1 hash over the octet stream resulting from using the Exclusive XML canonicalization defined for XML Signature [*XML-Signature [p.25]*].

In the example below two policies include and extend a common policy. In the first example there is a single policy document containing two policy assertions. The expression is given an identifier but not a fully qualified location. The second and third expressions reference the first expression by URI indicating the referenced expression is within the document.

```
(01) <wsp:Policy
       xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
       xmlns:wsp="http://www.w3.org/2006/07/ws-policy"
       xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
       wsu:Id="Protection" >
(02)   <sp:EncryptSignature wsp:Optional="true" />
(03)   <sp:ProtectTokens wsp:Optional="true" />
(04) </wsp:Policy>

(01) <wsp:Policy
       xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
       xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)   <wsp:PolicyReference URI="#Protection" />
(03)   <sp:OnlySignEntireHeadersAndBody />
(04) </wsp:Policy>

(01) <wsp:Policy
       xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
       xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
(02)   <sp:IncludeTimestamp />
(03)   <wsp:PolicyReference URI="#Protection" />
(04)   <sp:OnlySignEntireHeadersAndBody />
(05) </wsp:Policy>
```

There are times when it is desirable to "re-use" a portion of a policy expression. Generally, this can be accomplished by placing the common assertions in a separate policy expression and referencing it.

4.4 Policy Intersection

Policy intersection is useful when two or more parties express policy [p.6] and want to limit the policy alternatives [p.6] to those that are mutually compatible. For example, when a requester and a provider express requirements on a message exchange, intersection identifies compatible policy alternatives (if any) included in both requester and provider policies. Intersection is a commutative, associative function that takes two policies and returns a policy.

Because the set of behaviors indicated by a policy alternative [p.6] depends on the domain-specific semantics of the collected assertions, determining whether two policy alternatives are compatible generally involves domain-specific processing. As a first approximation, an algorithm is defined herein that approximates compatibility in a domain-independent manner; specifically, for two policy alternatives to be compatible, they must at least have the same vocabulary (see Section **3.2 Policy Alternative** [p.7]).

- Two policy assertions [p.6] are compatible if they have the same type [p.6] and
- If either assertion contains a nested policy expression [p.6] , the two assertions are compatible if they both have a nested policy expression and the alternative in the nested policy expression of one is compatible with the alternative in the nested policy expression of the other.

Assertion parameters [p.6] are not part of the compatibility determination defined herein but may be part of other, domain-specific compatibility processing.

- Two policy alternatives [p.6] are compatible if each assertion in one is compatible with an assertion in the other, and vice-versa. If two alternatives are compatible, their intersection is an alternative containing all of the assertions in both alternatives.
- Two policies [p.6] are compatible if an alternative in one is compatible with an alternative in the other. If two policies are compatible, their intersection is the set of the intersections between all pairs of compatible alternatives, choosing one alternative from each policy. If two policies are not compatible, their intersection has no policy alternatives.

As an example of intersection, consider two input policies in normal form:

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
       <!-- Policy P1 -->
(02)   <wsp:ExactlyOne>
(03)     <wsp:All> <!-- Alternative A1 -->
(04)       <sp:SignedElements>
(05)         <sp:XPath>/S:Envelope/S:Body</sp:XPath>
(06)       </sp:SignedElements>
(07)       <sp:EncryptedElements>
(08)         <sp:XPath>/S:Envelope/S:Body</sp:XPath>
(09)       </sp:EncryptedElements>
(10)     </wsp:All>
```

```
(11)     <wsp:All> <!-- Alternative A2 -->
(12)       <sp:SignedParts>
(13)         <sp:Body />
(14)         <sp:Header
                Namespace="http://www.w3.org/2005/08/addressing" />
(15)       </sp:SignedParts>
(16)       <sp:EncryptedParts>
(17)         <sp:Body />
(18)       </sp:EncryptedParts>
(19)     </wsp:All>
(20)   </wsp:ExactlyOne>
(21) </wsp:Policy>
```

The listing above contains two policy alternatives. The first alternative, (Lines 03-10) contains two policy assertions. One indicates which elements should be signed (Lines 04-06); its type is `sp:SignedElements` (Line 04), and its parameters include an XPath expression for the content to be signed (Line 05). The other assertion (Lines 07-09) has a similar structure: type (Line 07) and parameters (Line 08).

The second alternative (Lines 11-19) also contains two assertions, each with type (Line 12 and Line 16) and parameters (Lines 13-14 and Line 17).

As this example illustrates, compatibility between two policy assertions is based on assertion type and delegates parameter processing to domain-specific processing.

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
       <!-- Policy P2 -->
(02)   <wsp:ExactlyOne>
(03)     <wsp:All> <!-- Alternative A3 -->
(04)       <sp:SignedParts />
(05)       <sp:EncryptedParts>
(06)         <sp:Body />
(07)       </sp:EncryptedParts>
(08)     </wsp:All>
(09)     <wsp:All> <!-- Alternative A4 -->
(10)       <sp:SignedElements>
(11)         <sp:XPath>/S:Envelope/S:Body</sp:XPath>
(12)       </sp:SignedElements>
(13)     </wsp:All>
(14)   </wsp:ExactlyOne>
(15) </wsp:Policy>
```

Because there is only one alternative (A2) in policy P1 with the same vocabulary — the assertions have the same type — as another alternative (A3) in policy P2, the intersection is a policy with a single alternative that contains all of the assertions in A2 and in A3.

```
(01) <wsp:Policy
        xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
        xmlns:wsp="http://www.w3.org/2006/07/ws-policy" >
       <!-- Intersection of P1 and P2 -->
(02)   <wsp:ExactlyOne>
(03)     <wsp:All>
(04)       <sp:SignedParts >
```

```
(05)          <sp:Body />
(06)          <sp:Header
                 Namespace="http://www.w3.org/2005/08/addressing" />
(07)        </sp:SignedParts>
(08)        <sp:EncryptedParts>
(09)          <sp:Body />
(10)        </sp:EncryptedParts>
(11)        <sp:SignedParts />
(12)        <sp:EncryptedParts>
(13)          <sp:Body />
(14)        </sp:EncryptedParts>
(15)      </wsp:All>
(16)    </wsp:ExactlyOne>
(17) </wsp:Policy>
```

Note that there are > 1 assertions of the type `sp:SignedParts` ; when the behavior associated with `sp:SignedParts` is invoked, the contents of both assertions are used to indicate the correct behavior. Whether these two assertions are compatible depends on the domain-specific semantics of the `sp:SignedParts` assertion. To leverage intersection, assertion authors are encouraged to factor assertions such that two assertions of the same assertion type are always (or at least typically) compatible.

5. Security Considerations

It is RECOMMENDED that policies and assertions be signed to prevent tampering.

Policies SHOULD NOT be accepted unless they are signed and have an associated security token to specify the signer has the right to "speak for" the scope containing the policy. That is, a relying party shouldn't rely on a policy unless the policy is signed and presented with sufficient credentials to pass the relying parties' acceptance criteria.

It should be noted that the mechanisms described in this document could be secured as part of a SOAP message [*SOAP 1.1 [p.24]* , *SOAP 1.2 Messaging Framework [p.24]*] using WS-Security [*WS-Security 2004 [p.23]*] or embedded within other objects using object-specific security mechanisms.

A. References

A.1 Normative References

[IETF RFC 2119]
Key words for use in RFCs to Indicate Requirement Levels, S. Bradner, Author. Internet Engineering Task Force, June 1999. Available at http://www.ietf.org/rfc/rfc2119.txt.

[IETF RFC 3986]
Uniform Resource Identifier (URI): Generic Syntax, T. Berners-Lee, R. Fielding, and L. Masinter, Authors. Internet Engineering Task Force, January 2005. Available at http://www.ietf.org/rfc/rfc3986.txt.

[WS-Security 2004]
Web Services Security: SOAP Message Security 1.0 (WS-Security 2004), A. Nadalin, C. Kaler, P. Hallam-Baker, and R. Monzillo, Editors. Organization for the Advancement of Structured Information Standards, March 2004. Available at

http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf.

[XML 1.0]
Extensible Markup Language (XML) 1.0 (Third Edition), T. Bray, J. Paoli, C. M. Sperberg-McQueen, and E. Maler, Editors. World Wide Web Consortium, 4 February 2004. This version of the XML 1.0 Recommendation is http://www.w3.org/TR/2004/REC-xml-20040204. The latest version of XML 1.0 is available at http://www.w3.org/TR/REC-xml.

[XML Information Set]
XML Information Set (Second Edition), J. Cowan and R. Tobin, Editors. World Wide Web Consortium, 4 February 2004, revised 24 October 2001. This version of the XML Information Set Recommendation is http://www.w3.org/TR/2004/REC-xml-infoset-20040204. The latest version of XML Information Set is available at http://www.w3.org/TR/xml-infoset.

[XML Namespaces]
Namespaces in XML, T. Bray, D. Hollander, and A. Layman, Editors. World Wide Web Consortium, 14 January 1999. This version of the XML Information Set Recommendation is http://www.w3.org/TR/1999/REC-xml-names-19990114. The latest version of Namespaces in XML is available at http://www.w3.org/TR/REC-xml-names.

[XML Schema Structures]
XML Schema Part 1: Structures Second Edition, H. Thompson, D. Beech, M. Maloney, and N. Mendelsohn, Editors. World Wide Web Consortium, 28 October 2004. This version of the XML Schema Part 1 Recommendation is http://www.w3.org/TR/2004/REC-xmlschema-1-20041028. The latest version of XML Schema Part 1 is available at http://www.w3.org/TR/xmlschema-1.

[XML Schema Datatypes]
XML Schema Part 2: Datatypes Second Edition, P. Byron and A. Malhotra, Editors. World Wide Web Consortium, 28 October 2004. This version of the XML Schema Part 2 Recommendation is http://www.w3.org/TR/2004/REC-xmlschema-2-20041028. The latest version of XML Schema Part 2 is available at http://www.w3.org/TR/xmlschema-2.

A.2 Other References

[SOAP 1.1]
Simple Object Access Protocol (SOAP) 1.1, D. Box, et al, Editors. World Wide Web Consortium, 8 May 2000. Available at http://www.w3.org/TR/2000/NOTE-SOAP-20000508/.

[SOAP 1.2 Messaging Framework]
SOAP Version 1.2 Part 1: Messaging Framework, M. Gudgin, M. Hadley, N. Mendelsohn, J-J. Moreau, H. Frystyk Nielsen, Editors. World Wide Web Consortium, 24 June 2003. This version of the SOAP Version 1.2 Part 1: Messaging Framework Recommendation is http://www.w3.org/TR/2003/REC-soap12-part1-20030624/. The latest version of SOAP Version 1.2 Part 1: Messaging Framework is available at http://www.w3.org/TR/soap12-part1/.

[UDDI API 2.0]
UDDI Version 2.04 API, T. Bellwood, Editor. Organization for the Advancement of Structured Information Standards, 19 July 2002. This version of UDDI Version 2.0 API is http://uddi.org/pubs/ProgrammersAPI-V2.04-Published-20020719.htm. The latest version of the UDDI 2.0 API is available at http://uddi.org/pubs/ProgrammersAPI_v2.htm.

[UDDI Data Structure 2.0]
UDDI Version 2.03 Data Structure Reference, C. von Riegen, Editor. Organization for the Advancement of Structured Information Standards, 19 July 2002. This version of UDDI Version 2.0 Data

Structures is http://uddi.org/pubs/DataStructure-V2.03-Published-20020719.htm. The latest version of the UDDI 2.0 Data Structures is available at http://uddi.org/pubs/DataStructure_v2.htm.

[UDDI 3.0]

UDDI Version 3.0.1, L. Clément, et al, Editors. Organization for the Advancement of Structured Information Standards, 14 October 2003. This version of the UDDI Version 3.0 is http://uddi.org/pubs/uddi-v3.0.1-20031014.htm. The latest version of the UDDI 3.0 specification is available at http://uddi.org/pubs/uddi_v3.htm.

[Web Services Policy Attachment]

Web Services Policy 1.5 - Attachment, A. S. Vedamuthu, D. Orchard, M. Hondo, T. Boubez and P. Yendluri, Editors. World Wide Web Consortium, 31, July 2006. This version of the specification of the Web Services Policy 1.5 - Attachment specification is http://www.w3.org/TR/2006/WD-ws-policy-attach-20060731. The latest version of Web Services Policy 1.5 - Attachment is available at http://www.w3.org/TR/ws-policy-attach.

[WS-SecurityPolicy]

WS-SecurityPolicy v1.0, A. Nadalin, M. Gudgin, A. Barbir, and H. Granqvist, Editors. Organization for the Advancement of Structured Information Standards, 8 December 2005. Available at http://www.oasis-open.org/committees/download.php/15979/oasis-wssx-ws-securitypolicy-1.0.pdf.

[WSDL 1.1]

Web Services Description Language (WSDL) 1.1, E. Christensen, et al, Authors. World Wide Web Consortium, March 2001. Available at http://www.w3.org/TR/2001/NOTE-wsdl-20010315.

[WSDL 2.0 Core Language]

Web Services Description Language (WSDL) Version 2.0 Part 1: Core Language, R. Chinnici, J. J. Moreau, A. Ryman, S. Weerawarana, Editors. World Wide Web Consortium, 27 March 2006. This version of the WSDL 2.0 specification is http://www.w3.org/TR/2006/CR-wsdl20-20060327. The latest version of WSDL 2.0 is available at http://www.w3.org/TR/wsdl20.

[XML-Signature]

XML-Signature Syntax and Processing, D. Eastlake, J. Reagle, and D. Solo, Editors. The Internet Society & World Wide Web Consortium, 12 February 2002. This version of the XML-Signature Syntax and Processing Recommendation is http://www.w3.org/TR/2002/REC-xmldsig-core-20020212/. The latest version of XML-Signature Syntax and Processing is available at http://www.w3.org/TR/xmldsig-core/.

B. Acknowledgements (Non-Normative)

This document is the work of the W3C Web Services Policy Working Group.

Members of the Working Group are (at the time of writing, and by alphabetical order): Dimitar Angelov, Abbie Barbir, Charlton Barreto, Toufic Boubez (Layer 7 Technologies), Paul Cotton (Microsoft Corporation), Jeffrey Crump, Glen Daniels, Ruchith Fernando (WSO2), Christopher Ferris, William Henry, Frederick Hirsch, Maryann Hondo, Tom Jordahl, Philippe Le Hégaret (W3C/MIT), Jong Lee (BEA Systems, Inc.), Mark Little (JBoss Inc.), Ashok Malhotra, Monica Martin, Jeff Mischkinsky, Dale Moberg, Anthony Nadalin, David Orchard (BEA Systems, Inc.), Bijan Parsia (University of Manchester), Fabian Ritzmann, Daniel Roth (Microsoft Corporation), Sanka Samaranayake (WSO2), Felix Sasaki (W3C/Keio), Seumas Soltysik, Yakov Sverdlov (Computer Associates), Asir Vedamuthu (Microsoft Corporation), Sanjiva Weerawarana (WSO2), Ümit Yalçinalp, Prasad Yendluri.

The people who have contributed to discussions on public-ws-policy@w3.org are also gratefully acknowledged.

C. Web Services Policy 1.5 - Framework Change Log (Non-Normative)

Date	Author	Description
20060712	ASV	Updated the list of editors. Completed action items 12, 16 and 20 from the Austin F2F.
20060718	DBO	Completed action items: RFC2606 for domain names 09 (note: PLH had already done but it didn't show up in the change log)
20060726	ASV	Incorporated the XML namespace URI versioning policy adopted by the WG.